



STANDARD MANUAL STACKER

Ideal and economic choice for manual transport and lifting, with its different mast options (1600, 2500, 3000 mm) and diverse lifting capacity (500kg, 1000kg, 1500kg) enables to deal with a large number of applications in the warehouse or any other facilities. For example, with the lift capacity of 1000 kg and lifting height of 1600 mm, therefore the truck is an ideal and economic choice suitable for first level stacking.

Hand Stacker		1KG=2.2LB 1INCH=25.4MM		
ITEM/TYPE		SFH10	SFH15	SFHD10
Capacity Q	Kg	1000	1500	1000
Min. fork height h ₀	mm	85	85	85
Max. fork height h ₁	mm	1600	1600	2500
Min.mast height h ₂	mm	1980	1980	1830
Size of fork e's	mm	150/160x60	150/160x60	150/160x60
Length of fork L	mm	900/1150	300/1150	900/1150
Width of overall fork (adjust/fixed) b5	mm	330-740/550	330-740/550	330-740/550
Radius of gyration	mm	1250/1380	1250/1380	1250/1380
Weight	Kg	220	260	300
Fork rollers	mm	φ74x70	φ74x70	φ74x70
Big wheel	mm	φ180x50	φ180x50	φ180x50

Conforms to EN1757-1



- Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller.
- Optional choice of fixed fork (550X1150mm) and adjustable fork (330-740X900mm).
- We can offer additional protection for the operator through foot protection on the steering rollers.
- Safe parking in any situation with mechanical parking brake.
- Optional tiller pumping lifting and foot pedal lifting

